



CLEVERTRONICS LP ARGONAUT PRO WIDE BODY MAINTAINED WEATHERPROOF BATTEN WITH INTEGRAL BATTERIES & MICROWAVE SENSOR WITH HI/LO FUNCTION



PRODUCT INFORMATION

Catalogue Number	CWB4LEDM-P-WB-IB-PRO-MS-HL
Description	LP Premium, 4ft Argonaut PRO LED Weatherproof Batten with Integral Batteries and Microwave Sensor Control of the Lamps (Hi/Lo function), Enabled with Clevertest Plus
Construction	Glass Fibre Reinforced (GRP) Base, Polycarbonate Diffuser with Powder coated Metal Gear Tray and Stainless Steel clips
Mounting	Surface Mount
Dimensions L x W x H	1272mm x 158mm x 100mm
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 6.4V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Ballast	MerryTek MLC40C-P5
Lamp(s)	LED module, 4,000K Natural White, Ra>80, 44,000h Life [L80/B20 Ta 40°C], 50,000h Life [L70/B10 Ta 40°C]
Operating Voltage	240V AC; 50Hz
Total lumen output	4080 lm @ 123lm/W (based on the non-emergency version) - Default 3100 lm @ 115lm/W (Selectable during installation by dip switch on driver) - Low output mode
Power Consumption	35 Watts (Standby lamps max), 6.7 Watts (Standby lamps min)
IP Rating	IP66
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D125 C ₉₀ =D40
Impact Rating	IK07 (Base), IK09 (Diffuser)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550260	BATT:LP 6.4V 3200mAh 200mm lead.SBS.
8002670	PCA:40 LED Strip 600mm for Argonaut PRO
1330080	LED Driver - Sensor, MLC40-P5
CCPLED-48V95C-CKIT	LED Power Pack, 48V 95mA, LP

