

CLEVERTRONICS LP LED WEATHERPROOF SUPALITE (ZONWORKS XTHIVE)



PRODUCT INFORMATION

Catalogue Number	CWFLED-HV
MIC	AUE02820010001
Description	LP Premium LED Weatherproof Supalite Flood Emergency Light
Construction	Polycarbonate
Mounting	Surface Wall Mount (hard wired supply connection)
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm.
Weight	3.6kg
Operating Mode	Non-maintained
Testing System	Zoneworks XTHIVE (RF)
Battery	Lithium Iron Phosphate, 6.4V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED Heads (adjustable), 600lm per lamp head
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 5.4 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550290	BATT:LP 6.4V 3.2Ah.200mm lead.Stick.Brkt
CCPLED-WP-18V625C-CKIT	LED Power Pack, 18V 625mA, IP Loom, LP
1100550	WP Led Head, c/w Led's & Loom
800319x	PCA: RF Node CT10678-Ax internal antenna, Horizontal

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order