



CLEVERTRONICS ECONOMY LITHIUM WIRE GUARD BATTEN



PRODUCT INFORMATION

Catalogue Number	EBS128S-WG-LI
Description	1 x 28 Watt Economy Lithium Wire Guard Batten with LED Emergency POD
Construction	Powder coated Steel body and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Wire Guard
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T5 Cool White Tri-Phosphorous 28W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	32 Watts (Lamp ON), 0.4 Watts (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
3100210	28w/840 T5, Coolwhite Lamp
ELIFE-X-LI-CKIT-NP	Lifelight, Control Only, 3.0Ah, No Plug

