



## CLEVERTRONICS ECONOMY LITHIUM DIFFUSED BATTEN



### PRODUCT INFORMATION

Catalogue Number	EBS236S-DIF-LI
Description	2 x 36 Watt Economy Lithium Diffused Batten with LED Emergency POD
Construction	Powder coated Steel body, Acrylic Prismatic Diffuser and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T8 Cool White Tri-Phosphorous 36W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	71 Watts (Lamp ON), 0.4 Watts (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
3100380	36w/840 Coolwhite Lamp (2)
ELIFE-X-LI-CKIT-NP	Lifelight, Control Only, 3.0Ah, No Plug

