



## CLEVERTRONICS ECONOMY LITHIUM LED TUBE DIFFUSED BATTEN



### PRODUCT INFORMATION

Catalogue Number	EBS2L2S-DIF-LI
Description	Economy Lithium 2x LED tube 2ft Diffused Batten with LED Emergency POD
Construction	Powder coated Steel body with Acrylic Prismatic Diffuser and PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Lamp(s)	2x Philips Essential LEDtube T8, Col. 840, 30,000hours
Operating Voltage	240V AC; 50Hz
Total lumen output	1365 lm @ 85lm/W
Power Consumption	16 Watts (Lamp ON), 0.4 Watts (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
3170030	LED TUBE 8W/840, 0.6m
ELIFE-X-LI-CKIT-NP	Lifelight, Control Only, 3.0Ah, No Plug

