



**FWB4LED-P-MS-HL**

## CLEVERTRONICS 240V ARGONAUT LED WEATHERPROOF BATTEN WITH HI/LO FUNCTION



### PRODUCT INFORMATION

Catalogue Number	FWB4LED-P-MS-HL
Description	240V Argonaut Weatherproof Batten and Microwave Sensor Control of the Lamps (10% - 100%)
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless Steel clips
Mounting	Surface Mount
Dimensions L x W x H	1160mm x 110mm x 108mm
Diffuser	Polycarbonate
LED Driver	MerryTek MLC65C-P4
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	4125 lm @ 96lm/W
Power Consumption	44 Watts (Standby lamps max), 5.6 Watts (Standby lamps min)
IP Rating	IP66
Operating Temperature	0°C to 40°C
Impact Rating	IK08

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330090	LED MSHL Driver - 65w 600-1200mA, 35-55V
8002690	PCA:LED Strip Argonaut Standard inc tray

**240V**