

## CLEVERTRONICS L10 DIFFUSED PRO BATTEN (DLI)



### PRODUCT INFORMATION

Catalogue Number	LBS114S-DIF-A2-DLI
Description	1 x 14 Watt L10 Optimum, PRO Diffused Batten with LED Emergency POD
Construction	Powder coated Steel body, Acrylic Prismatic Diffuser and ABS/Polycarbonate End Caps
Mounting	Surface mount
Dimensions L x W x H	720mm x 160mm x 105mm
Operating Mode	Sustained
Testing System	DLI compatible
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T5 Cool White Tri-Phosphorous 14W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	16 Watts (Lamps on), 0.4 Watts (Lamps off)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D63 C <sub>90</sub> =D63

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
3100010	14w/840 T5, Coolwhite Tube
1310060	1x14-35w Elect Ballast Multiwatt, A2
LLIFE-PRO-CKIT-DLI-NP	LifelightPro,ControlOnly,Batten,DLI,L10
8002200	PCA:DLI Node, #CT10410-A3

