

CLEVERTRONICS L10 DIFFUSED PRO BATTEN (Zoneworks)



PRODUCT INFORMATION

Catalogue Number	LBS128M-DIF-A2-ZW
Description	1 x 28 Watt L10 Optimum, Pro diffused batten with maintained LED emergency POD
Construction	Powder coated steel body, acrylic prismatic diffuser and ABS/polycarbonate end caps
Mounting	Surface mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Maintained LED POD function (LEDs permanently on for low level comfort light).
Testing System	Zoneworks computerised testing
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Ballast	Electronic, EEI=A2
Lamp(s)	T5 Cool White Tri-Phosphorous 28W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	34 Watts (lamp on), 2.4 Watts (lamps off)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
3100210	1x14-35w Elect Ballast Multiwatt, A2
1120212	28w/840 T5, Coolwhite Lamp
LLIFEM-PRO-CKIT-ZW-NP	Lampholder 28/35w T8>T5 Adapt,T/S1120215
8001450	Lifelight Pro,Control Only, MNT, ZW, L10

ZONEWORKS

L10 OPTIMUM
LITHIUM BATTERY RANGE

Version: July 2016-I

www.clevertronics.com.au