



CLEVERTRONICS L10 DIFFUSED PRO BATTEN



PRODUCT INFORMATION

Catalogue Number	LBS128S-DIF-A2
Description	1 x 28 Watt L10 Optimum, PRO Diffused Batten with LED Emergency POD
Construction	Powder coated Steel body, Acrylic Prismatic Diffuser and ABS/Polycarbonate End Caps
Mounting	Surface mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Weight	3.7kg
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T5 Cool White Tri-Phosphorous 28W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	32 Watts (Lamp on), 0.4 Watts (Lamps off)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
3100210	28w/840 T5, Coolwhite Lamp
1120212	Lampholder 28/35w T8>T5 Adapt,T/S1120215
LLIFE-PRO-CKIT-ZW-NP	LifelightPro,ControlOnly,Batten, ZW, L10

