



CLEVERTRONICS L10 LED TUBE DIFFUSED BATTEN (DLI)



PRODUCT INFORMATION

Catalogue Number	LBS1L2S-DIF-DLI
Description	L10 Optimum 1x LED tube diffused batten with LED emergency POD
Construction	Powder coated steel body, acrylic prismatic diffuser and ABS/polycarbonate end caps
Mounting	Surface mount
Dimensions L x W x H	720mm x 160mm x 105mm
Operating Mode	Sustained
Testing System	DLI compatible
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Lamp(s)	1 x 600mm LED tube, Col. 840, 8W/880 lm per tube, 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	8 Watts (lamps ON), 0.4 Watts (lamps OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
3170025	LED TUBE 8W 4000K, 0.6m, 60°C
1120320	LAMPHOLDER, t/s T8 Sabre Battens, 2 Part
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8002200	PCA:DLI Node, #CT10410-A3

