



CLEVERTRONICS L10 DIFFUSED PRO BATTEN



PRODUCT INFORMATION

Catalogue Number	LBS228M-DIF-A2
Description	2 x 28 Watt L10 Optimum diffused Pro batten with maintained LED emergency POD
Construction	Powder coated steel body, acrylic prismatic diffuser and ABS/polycarbonate end caps
Mounting	Surface mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Ballast	Electronic, EEI=A2
Lamp(s)	T5 Cool White Tri-Phosphorous 28W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	65 Watts (lamp on), 2.4 Watts (lamps off)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
3100210	28w/840 T5, Coolwhite Lamp
1120212	Lampholder 28/35w T8>T5 Adapt,T/S1120215
LLIFEM-PRO-CKIT-NP	LLIFEM-PRO-CKIT-NP



Version: July 2016-I

www.clevertronics.com.au

