

CLEVERTRONICS L10 DIFFUSED PROFESSIONAL BATTEN & MICROWAVE SENSOR (DLI)



PRODUCT INFORMATION

Catalogue Number	LBS236M-DIF-A2-MS-DLI
Description	2 x 36 Watt L10 Optimum, Professional Diffused Batten with Maintained LED Emergency POD and Microwave Sensor Control of the Lamps (on/off)
Construction	Powder coated Steel body, Acrylic Prismatic Diffuser and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Maintained LED POD function (LEDs permanently on for low level comfort light).
Testing System	DLI compatible
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T8 Cool White Tri-Phosphorous 36W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	70 Watts (Lamp on), 2.4 Watts (Lamps off)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
1310224	2x36w Electronic Ballast, A2
3100380	36w/840 Coolwhite Lamp
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8002200	PCA:DLI Node, #CT10410-A3

