



CLEVERTRONICS 2 x 36W DIFFUSED BATTEN WITH MICROWAVE MOTION SENSOR CONTROL AND LED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	LBS236M-DIF-A2-MS
Description	2 x 36 Watt Diffused Batten with Motion Sensor Control and LED Emergency
Construction	Powder Coated Steel body with Polycarbonate lamp holders.
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Maintained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Prismatic
Ballast	Electronic , 2x36W, EEI=A2
Lamp(s)	T8 Cool White Tri-Phosphorous 36W/840
Operating Voltage	240V
Power Consumption	81.4 Watts (lamps ON) 6.4 Watts (lamps OFF)
IP Rating	IP20
Operating Temperature	10° to 40°C
AS2293 Classification	C0=D63 C90=C63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310224	Ballast, Philips HF-P, 2 x36W, EEI=A2
3100380	Lamp(s) T8 Cool White Tri-Phosphor 36W/840
1120320	Lamp Holder T8
2300110	Diffuser 28/36W Wide
2900012	End Caps
1190116	Motion Sensor Assembly
8002390	Driver, PCA:L10/LP Lifelight Pro, Zoneworks Compatible 400mA Output
3760210	Emergency End Cap control