



CLEVERTRONICS L10 OPTIMUM CLEVERFIT LED THEATRE EXIT (DLI)



PRODUCT INFORMATION

Catalogue Number	LCFLED-TH-DLI-DS-R
Description	LED L10 OPTIMUM Cleverfit Theatre Double Sided Exit, 24 metre viewing Distance
Construction	ABS Body with ABS Diffuser and Polycarbonate Clear tamper proof cover.
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Operating Mode	Maintained
Testing System	DLI Compatible
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Theatre Mask (must specify diffuser combination)
Lamp(s)	6 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar - 100,000 hour
Operating Voltage	240V 50Hz
Power Consumption	2.7W Standby (4.7W during first 16hr charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZS2293 Classification	NA – Theatre Mask

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery: 3.3 Volt 2.5Ah Li-ion
8002330	PCA: L10 LED Cleverfit Driver, #CT10164-L4
8002430	PCA: L10 DLED Cleverfit Light Strip, #CT10166-D1
8002200	PCA: DLI Node, #CT10410-A3

