

CLEVERTRONICS L10 CLASSIC WEATHERPROOF EXIT



PRODUCT INFORMATION

Part Number	LCWELED-R
Description	L10 Lithium Nanophosphate Classic weatherproof Emergency EXIT, Enabled with Clevertest Plus
Construction	Polycarbonate clear cover, glass reinforced nylon PA66 base
Mounting	Wall, Ceiling single-Sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.4 Watts (Standby), 4.8 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D8 C ₉₀ =D6.3
Impact Rating	IK10
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP

