



CLEVERTRONICS L10 JUMBO LED EXIT UNIVERSAL MOUNT (Zoneworks)



PRODUCT INFORMATION

| | |
|-----------------------|---|
| Catalogue Number | LJELED-40-ZW |
| Description | L10 Optimum Jumbo Emergency Exit |
| Construction | Powder coated Metal Frame with Acrylic Diffuser |
| Mounting | Surface Mount |
| Dimensions L x W x H | 630mm x 100mm x 320mm |
| Weight | 7.3kg |
| Operating Mode | Maintained |
| Testing System | Zoneworks computerised testing |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | All pictograph directional inserts included in the box (One box solution) |
| Lamp(s) | 12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 3.2 Watts (Standby), 5.6 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =D6.3 C ₉₀ =E3.2 |
| Viewing Distance | 40m |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|--------------------|--|
| 1530010 | BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT. |
| LJELED-40-CKIT-110 | Jumbo LED Exit, Control Kit, L10 |
| 8002470 | PCA:Duris E5 Strip for LJELED.CT10050-D1 |
| 8001450 | PCA:Powerline Node ZW, #CT10310-A6 |

