



## CLEVERTRONICS L10 JUMBO LED EXIT UNIVERSAL MOUNT



### PRODUCT INFORMATION

|                       |   |
|-----------------------|---|
| Catalogue Number      | LJELED-40   |
| Description           | L10 Optimum Jumbo Emergency Exit, Enabled with Clevertest Plus                    |
| Construction          | Powder coated Metal Frame with Acrylic Diffuser                                   |
| Mounting              | Surface Mount   |
| Dimensions L x W x H  | 630mm x 100mm x 320mm   |
| Weight                | 7.3kg   |
| Operating Mode        | Maintained  |
| Testing System        | Clevertest Plus Enabled (Not activated by default)                                |
| Battery               | Lithium Nanophosphate, 3.3V 2500mAh   |
| Charging Method       | Intelligent Current Limited Constant Voltage                                      |
| Diffuser              | All pictograph directional inserts included in the box (One box solution)         |
| Lamp(s)               | 12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs |
| Operating Voltage     | 240V AC; 50Hz   |
| Power Consumption     | 3.2 Watts (Standby), 5.6 Watts (Max)  |
| IP Rating             | IP20  |
| Operating Temperature | 1°C to 40°C   |
| AS2293 Classification | C <sub>0</sub> =D6.3 C <sub>90</sub> =E3.2  |
| Viewing Distance      | 40m   |

### REPLACEMENT PARTS

| PART NUMBER        | DESCRIPTION                              |
|--------------------|--|
| 1530010            | BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT. |
| LJELED-40-CKIT-110 | Jumbo LED Exit, Control Kit, L10         |
| 8002470            | PCA:Duris E5 Strip for LJELED.CT10050-D1 |

