



CLEVERTRONICS L10 OPTIMUM JUMBO WEATHERPROOF EXIT WALL MOUNT (DALI)



PRODUCT INFORMATION

Catalogue Number	LJWELED-40-DALI-WM-R
Description	L10 Optimum Wall Mount IP66/67 Jumbo Weatherproof Exit
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Wall Mount
Dimensions L x W x H	130mm x 560mm x 280mm
Weight	5.5kg
Operating Mode	Maintained
Testing System	DALI compatible
Battery	Lithium Nanophosphate
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man (must specify diffuser combination)
Lamp(s)	4 x (5 x high intensity, low energy LED), Surface Mounted onto a Replaceable Lamp Bar - 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 5.3 (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =E1.6 C ₉₀ =E1.25
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	40m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.
8002396	PCA:L/CJWELED-40 Driver # CT10142-L5
8002122	PCA:Duris E5 LED Strip 5LED ,CT10152-D3
8002200	PCA:DALI Node, #CT10410-A3

DALI EM**L10** LITHIUM
NANOPHOSPHATE®
OPTIMUM
NOTHING ELSE COMPETES WITH NANOPHOSPHATE®