



## LJWELED-40-WM-R

CLEVERTRONICS L10 JUMBO WEATHERPROOF WALL MOUNT EXIT



| PRODUCT INFORMATION      |  |
|--------------------------|--|
| Part Number              | LJWELED-40-WM-R  |
| MIC                      | AUA01320030001   |
| Description              | L10 Optimum Wall Mount IP66/67 Jumbo Weatherproof Exit, Enabled with Clevertest Plus |
| Construction             | Base material: Polycarbonate<br>Diffuser cover material: Polycarbonate               |
| Mounting                 | Wall mount   |
| Dimensions L x W x H     | 560mm x 130mm x 280mm  |
| Weight                   | 5.5kg  |
| Operating Mode           | Maintained   |
| Testing System           | Clevertest Plus Enabled (Not activated by default)                                   |
| Battery                  | Lithium Nanophosphate, 3.3V 2500mAh  |
| Charging Method          | Intelligent current limited constant voltage   |
| Diffuser                 | Running man (Must specify diffuser combination)                                      |
| Lamp(s)                  | 4 x 5 high intensity, surface mounted onto a replaceable lamp bar – 100,000hour      |
| Operating Voltage        | 240V AC; 50Hz  |
| Power Consumption        | 2.8 Watts (Standby), 5.3 Watts (Max)   |
| IP Rating                | IP66/IP67  |
| IK Rating                | IK08 (side surface) IK09 (front surface)   |
| Operating Temperature    | 0°C to 40°C  |
| AS2293 Classification    | C <sub>0</sub> =E1.6 C <sub>90</sub> =E1.25  |
| Viewing Distance         | 40m  |
| Applicable Standards     | AS/NZS3820, CISPR15, AS/NZS2293.3  |
| Compliance Marking (RCM) |  |

| REPLACEMENT PARTS                 |   |
|-----------------------------------|---|
| PART NUMBER                       | DESCRIPTION                                     |
| 1530010                           | BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.        |
| 8002122                           | PCA:Duris E5 LED Strip 5LED ,CT10152-D3 (Qty 4) |
| AUM01370060001<br>LJWELED-40-CKIT | WP LED Exit, Control Kit, L10, OWC              |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.