



CLEVERTRONICS L10 OPTIMUM JUMBO WEATHERPROOF EXIT WALL MOUNT (Zoneworks)



PRODUCT INFORMATION

Catalogue Number	LJWELED-40-ZW-WM-R
Description	L10 Optimum Wall Mount IP66/67 Jumbo Weatherproof Exit
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Wall Mount
Dimensions L x W x H	130mm x 560mm x 280mm
Weight	5.5kg
Operating Mode	Maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man (must specify diffuser combination)
Lamp(s)	4 x (5 x high intensity, low energy LED), Surface Mounted onto a Replaceable Lamp Bar - 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 5.3 (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =E1.6 C ₉₀ =E1.25
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	40m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.
LJWELED-40-CKIT	WP LED Exit, Control Kit, L10
8002122	PCA:Duris E5 LED Strip 5LED ,CT10152-D3
8001450	PCA:Powerline Node ZW, #CT10310-A6

ZONEWORKS**L10** LITHIUM
NANOPHOSPHATE®

OPTIMUM

NOTHING ELSE COMPETES WITH NANOPHOSPHATE®