



LJWELED-WM-40-IPREM-R

CLEVERTRONICS L10 JUMBO WEATHERPROOF WALL MOUNT EXIT WITH REMOTE CONTROL GEAR



PRODUCT INFORMATION	
Part Number	LJWELED-WM-40-IPREM-R
MIC	AUA01320200001
Description	L10 Optimum Wall Mount IP66/67 Jumbo Weatherproof Exit with Remote Control Gear for Low Temperature Applications, Enabled with Clevertest Plus
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount
Dimensions L x W x H	EXIT Sign – 560mm x 130mm x 280mm Remote Control Gear – 380mm x 130mm x 190mm
Weight	5.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	4 x 5 high intensity, surface mounted onto a replaceable lamp bar – 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 5.3 Watts (Max)
IP Rating	IP66/IP67
IK Rating	IK08 (side surface) IK09 (front surface)
Operating Temperature	40°C to -40°C - Main enclosure with LED lamp bar 0°C to 40°C - Remote enclosure containing control pack and battery
AS2293 Classification	C ₀ =E1.6 C ₉₀ =E1.25
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.
8002122	PCA:Duris E5 LED Strip 5LED ,CT10152-D3 (Qty 4)
AUM01370060001 LJWELED-40-CKIT	WP LED Exit, Control Kit, L10, OWC

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.