

## CLEVERTRONICS L10 LIFELIGHT PRO SURFACE MOUNT



### PRODUCT INFORMATION

Catalogue Number	LLIFE-2PRO-SMS-1200
Description	L10 Optimum Lifelight PRO, high performance, surface mount twin emergency light with lithium battery technology
Mounting	Surface Mount
Dimensions L x W x H	1223mm x 112mm x 55mm
Operating Mode	Non-maintained
Testing System	N/A - Manual test switch
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Twin 2 x 3W LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D125 C <sub>90</sub> =D125

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
1100830	Lifelight Pro Head Assembly, Round



Version: July 2016-I

[www.clevertronics.com.au](http://www.clevertronics.com.au)