



## CLEVERTRONICS L10 LIFELIGHT PRO SURFACE MOUNT EMERGENCY



### PRODUCT INFORMATION

Catalogue Number	LLIFE-2PRO-SMS-CT-1200
Description	L10 Optimum LifeLight PRO, High Performance, Surface Mounted Twin Emergency Light
Construction	Powder Coated Metal Enclosure
Mounting	Surface Mount and can also be chain suspended
Dimensions L x W x H	1220mm x 110mm x 50mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 4.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D125 C <sub>90</sub> =D125

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
1100830	Lifelight Pro Head Assembly, Round

