



CLEVERTRONICS L10 LIFELIGHT PRO SURFACE MOUNT EMERGENCY (Zoneworks)



PRODUCT INFORMATION

Catalogue Number	LLIFE-2PRO-SMS-ZW-1200
Description	L10 Optimum LifeLight PRO, High Performance, Surface Mounted Twin Emergency Light with Lithium Battery Technology
Construction	Powder Coated Metal body
Mounting	Surface Mount and can also be chain suspended
Dimensions L x W x H	1220mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED (Lifetime warranty on the lamp head and loom assembly) (x2)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 4.4W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D125 C ₉₀ =D125

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
1100830	Lifelight Pro Head Assembly, Round
8001450	PCA:Powerline Node ZW, #CT10310-A6

ZONEWORKS**L10** LITHIUM
NANOPHOSPHATE®

OPTIMUM

NOTHING ELSE COMPETES WITH NANOPHOSPHATE®

Version: May 2017-I

www.clevertronics.com.au