



CLEVERTRONICS L10 OPTIMUM LIFELIGHT PRO SURFACE MOUNT EMERGENCY (ZONWORKS)



PRODUCT INFORMATION

Catalogue Number	LLIFE-2PRO-SMS-ZW-600
Description	Lifelight PRO, High Performance, Surface Mount Twin Emergency Light with Lithium Battery Technology
Mounting	Surface Mount and can also be chain suspended
Dimensions L x W x H	613mm x 112mm x 55mm
Ceiling hole cut-out	N/A
Minimum ceiling depth	N/A
Operating Mode	Non-Maintained
Testing System	Zoneworks Computerised Testing
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	Twin 2 x 3W LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V 50Hz
Power Consumption	0.8 Watts
IP Rating	IP20
Impact Rating	IK08
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C ₀ =D100 C ₉₀ =D100

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100830	Lamps: 2 x 3W LED Round Head Assembly - White
1530230	Battery: 3.3V 5Ah.Li-ion, 200mm lead with Bracket
LLIFE-PRO-CKIT	PCA: Lifelight Pro Control Gear
8001450	PCA: Zoneworks Powerline Node, #CT10310-A6

