

CLEVERTRONICS L10 LIFELIGHT EMERGENCY, BLACK (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	LLIFE-HV-BLK
MIC	AUD01810040002
Description	L10 Optimum Lifelight, High Performance, Recessed Emergency Light, Black
Construction	PC/ABS Head and Control Gear Enclosure
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (MAX)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, Brkt
AUM01870020001 LLIFE-CKIT-HV	Lifelight: LED, Control Only, L10, HV (incl. HIVE Node)
1100924	LIFELight Head Assembl, Round, LT, 1LED, Blk
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order