



LLIFE-HV

CLEVERTRONICS L10 LIFELIGHT RECESSED EMERGENCY



PRODUCT INFORMATION	
Part Number	LLIFE-HV
MIC	AUD01810010002
Description	L10 Optimum Lifelight, High Performance, Recessed Emergency Light
Construction	PC/ABS Head
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3W (Standby) 4.5W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530010	BATT:L10 3.3V 2500mAh 200mm lead,BRKT.
8050210	LED: HWSUB: HT10136-A3 - GW CSHPM 'LT'
AUM01870020001 LLIFE-CKIT-HV	Lifelight: LED, Control Only, L10, HV (incl HIVE Node)
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order