

CLEVERTRONICS L10 LIFELIGHT PRO RECESSED IP65 WEATHERPROOF EMERGENCY (DALI)



PRODUCT INFORMATION

Part Number	LLIFE-PRO-DALI-RECWP-WHT
MIC	AUT01220040102
Description	L10 Lithium Nanophosphate LifeLight PRO, high performance, IP65 recessed Emergency Light
Construction	Die Cast Aluminium Body 316 Stainless Steel Screws Clear Toughened Glass
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm head diameter
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz (supplied with a 2 core and earth flex and plug)
Power Consumption	0.4W (Standby), 4.7W (Max during 16hr charge)
IP Rating	IP65 (Lamp head only)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Impact Rating	IK10

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
AUM01270200002	Lifelight Pro, Control Only, L10
1100843	Lifelight Pro Head Assembly, Round, Blk, Gen 2
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order