



CLEVERTRONICS L10 LIFELIGHT PRO SQUARE, BLACK



PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-DALI-SQ-BLK
Description	L10 Optimum LifeLight PRO Square, High Performance, Recessed Emergency Light, Black
Construction	PC/ABS Head
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm x 60mm (Head)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	DALI compatible
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP/L10
1100835	Lifelight Pro Head Assembly, Round,Black
8002200	PCA:DALI Node, #CT10410-A3

