



LLIFE-PRO-HV-RECWP-WHT

CLEVERTRONICS L10 LIFELIGHT PRO IP65 WEATHERPROOF RECESSED EMERGENCY LIGHT - WHITE



PRODUCT INFORMATION

Part Number	LLIFE-PRO-HV-RECWP-WHT
MIC	AUT01820020002
Description	L10 Optimum LifeLight PRO, IP65 recessed Emergency Light, White
Construction	Die Cast Aluminium Body, 316 Stainless Steel Screws, Clear Toughened Glass
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm diameter (Lamp head)
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max during 16-hour charge)
IP Rating	IP65 (Lamp head only)
IK Rating	IK10 (Lamp head only)
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead, Brkt
1100817	Lifelight Pro Head Assembly, Round, LT, Blk, Gen 2
AUM01870010001 LLIFE-PRO-CKIT-HV	Lifelight Pro, Control Only, HV, L10 (incl. Hive node)
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order