

CLEVERTRONICS L10 PREMIUM LIFELIGHT PRO RECESSED EMERGENCY (ZONENWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-HV
MIC	AUT01810010002
Description	L10 Optimum LifeLight PRO, high performance, recessed Emergency Light
Construction	PC/ABS Head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (MAX)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
AUM01870010001 LLIFE-PRO-CKIT-HV	Lifelight Pro, Control Only, HV, L10 (incl. HIVE Node)
1100868	Lifelight Pro Head Assbly,Rnd,Large+Ring, LT,Gen 2
8003191	PCA: RF Node CT10678-A9 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order