

CLEVERTRONICS L10 LIFELIGHT PRO SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

| | |
|-----------------------|--|
| Catalogue Number | LLIFE-PRO-SM-HV |
| MIC | AUT01810030001 |
| Description | L10 Optimum Lifelight PRO, High Performance, Surface Mounted Emergency Light |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Weight | 0.7kg |
| Operating Mode | Non-maintained |
| Testing System | Zoneworks XT Hive (RF) |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 0.4W (Standby) 4.7W (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =D80 C ₉₀ =D80 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|---|
| 1530231 | BATTERY:L10 3.3V 5AH. 200mm lead.no Brkt |
| 8003191 | PCA: RF Node CT10678-A9 Int Antenna LLPro |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order