

## CLEVERTRONICS L10 LIFELIGHT PRO IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY (ZONENWORKS XT HIVE)



### PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SM-WP-HV
MIC	AUT01820070001
Description	L10 Optimum Lifelight PRO, High Performance, Weatherproof, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT Hive (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby) 3W (Max)
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	BATTERY:L10 3.3V 5AH. 200mm lead.no Brkt
8050170	LED: HWSUB: CT10668-D1
8002924	Driver: PCA: xLIFEPro SM #CT10142-L9 2C250/550 CTP AU
8003191	PCA: RF Node CT10678-A9 Int Antenna LLPro

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*