

CLEVERTRONICS L10 LIFELIGHT PRO SURFACE MOUNT EMERGENCY, BLACK



PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SM-ZW-BLK
MIC	AUT01110160001
Description	L10 Optimum Lifelight PRO, High Performance, Surface Mounted Emergency Light, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby), 2.7W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	BATTERY:L10 3.3V 5AH. 200mm lead.no Brkt
8001450	PCA:Powerline Node ZW, #CT10310-A6

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order