

CLEVERTRONICS L10 LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

| | |
|-----------------------|--|
| Catalogue Number | LLIFE-SM-WP |
| MIC | AUD01320010001 |
| Description | L10 Optimum Lifelight, Weatherproof, Surface Mounted Emergency Light, Enabled with Clevertest Plus |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 247mm x 129mm x 51mm |
| Weight | 0.8kg |
| Operating Mode | Non-maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | 1 x High intensity LED |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1W (Standby) 4.2W (Max) |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C ₀ =D40 C ₉₀ =D40 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|--|
| 1530071 | BATTERY:L10 3.3V 2.5AH 200mm ld, no Brkt |
| 8002938 | Driver: PCA: LLIFE CT10260-L5 1C550 CTP AU Vert Connectors |
| 8050174 | LED: PCA: HWSUB: CT10694-D1 |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order