

CLEVERTRONICS L10 LIFELIGHT, BLACK (ZONWORKS XT)



PRODUCT INFORMATION

Part Number	LLIFE-ZW-BLK
MIC	AUD01110040004
Description	L10 Lithium Nanophosphate Lifelight, recessed Emergency Light, Black
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.
AUM01170040001 LLIFE-CKIT-ZW	Lifelight: LED, Control Only, L10, ZW, OWC (Incl. ZW node)
1100924	LIFELight Head Assembl, Round, LT, 1LED, Blk
8001450	PCA:Powerline Node ZW, #CT10310-A6

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order