



## CLEVERTRONICS L10 MAINTAINED LIFELIGHT PRO RECESSED EMERGENCY (DALI)



### PRODUCT INFORMATION

Catalogue Number	LLIFEM-PRO-DALI
Description	L10 Optimum Maintained LifeLight PRO, High Performance, Recessed Emergency Light with Lithium Battery Technology
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 60mm Head Diameter (95mm with adaptor plate)
Ceiling hole cut-out	51mm, 85mm (with adaptor plate)
Minimum ceiling depth	200mm, 120mm (with adaptor plate)
Operating Mode	Maintained (LEDs permanently ON at 250mA - 182lm) Emergency mode (LEDs running at 550mA - 336lm)
Testing System	DALI compatible
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz (supplied with a 2 core and earth flex and plug)
Power Consumption	5.7 Watts (Standby), 8.3 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D63 C <sub>90</sub> =D63

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFEM-PRO-CKIT	Lifelight Pro,Control Only, MNT, L10
1100830	Lifelight Pro Head Assembly, Round
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

**L10** LITHIUM  
NANOPHOSPHATE®  
OPTIMUM  
NOTHING ELSE COMPETES WITH NANOPHOSPHATE®