



LLIFEM-PRO

CLEVERTRONICS L10 MAINTAINED LIFELIGHT PRO RECESSED EMERGENCY



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | LLIFEM-PRO |
| MIC | AUT01310150001 |
| Description | L10 Optimum Maintained Lifelight PRO, Recessed Emergency Light, Enabled with Clevertest Plus |
| Mounting | Recessed Ceiling |
| Dimensions L x W x H | 232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate) |
| Ceiling hole cut-out | 51mm (85mm with adaptor plate) |
| Minimum ceiling depth | 200mm (120mm with adaptor plate) |
| Operating Mode | Maintained (LED permanently on with no switch control) |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent current limited constant voltage charger |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V 50Hz |
| Power Consumption | 2.4W (Standby), 4.7W (Max during 16-hour charge) |
| IP Rating | IP20 |
| Operating Temperature | 1° to 40°C (Ambient) |
| AS2293 Classification | C ₀ =D80 C ₉₀ =D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-----------------------------------|--|
| 1530230 | Battery: 3.3V 5Ah.Li-ion, 200mm lead with Bracket |
| 1100868 | Lifelight Pro Head Assbly,Rnd,Large+Ring, LT,Gen 2 |
| AUM01370070001 LLIFEM-PRO-CKIT | Lifelight Pro,Control Only, MNT, L10, CTP, OWC |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order