

CLEVERTRONICS L10 ULTRABLADE PRO, THEATRE (ZONWORKS XT HIVE)



PRODUCT INFORMATION

| | |
|-----------------------|----------------------------------------------------------------------|
| Catalogue Number | LUBPRO-TH-HV-R |
| MIC | AUA01860090001 |
| Description | L10 Lithium Nanophosphate Ultrablade Pro blade Exit, Theatre |
| Construction | PC/ABS body with PC diffuser |
| Mounting | Recessed ceiling |
| Dimensions L x W x H | 317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate) |
| Ceiling Hole Cut-Out | 350mm x 48mm |
| Minimum Ceiling Depth | 80mm |
| Weight | 1.1kg |
| Operating Mode | Maintained |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Nanophosphate 3.3V 2.5Ah |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | Theatre mask, Running man (Must specify diffuser combination) |
| Lamp (s) | 12 x Duris E3 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1.4 Watts (Standby), 3.7 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | N/A |
| Viewing Distance | 24m |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|------------------------------------------|
| 1550050 | BATT:LP 3.3V 2.5Ah 70mm lead,no BRKT. |
| 8002178 | PCA:UBP LED strip PCB Assy (CT10602-Dx) |
| LUBPRO-CKIT | Ultrablade Pro,Control Only, L10 |
| 8003190 | PCA: RF Node CT10678-Ax internal antenna |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order