



LUBPRO-TH-R

CLEVERTRONICS L10 ULTRABLADE PRO
THEATER MASK



PRODUCT INFORMATION

Part Number	LUBPRO-TH-R
MIC	AUA01310310001
Description	L10 Ultrablade Pro Recessed Blade Exit with Theatre Mask, Enabled with Clevertest Plus
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask, Running Man, Single Sided
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead, no Brkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
AUM01370010001 LUBPRO-CKIT	Ultrablade Pro, Control Only, CT10142-L9, L10

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.