



CLEVERTRONICS L10 PROFESSIONAL WEATHERPROOF BATTEN



Gen 1



Gen 2

PRODUCT INFORMATION

Catalogue Number	LWB128S-P-A2-DALI
Description	1 x 28 Watt L10 Optimum Professional Weatherproof Batten with LED Emergency POD
Construction	Polycarbonate Base and Diffuser with Powdercoated Metal Gear Tray and Tamper proof Stainless Steel clips
Mounting	Surface Mount
Dimensions L x W x H	1330mm x 160mm x 110mm
Weight	3.7kg
Operating Mode	Sustained
Testing System	DALI compatible
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T5 Cool White Tri-Phosphorous 28W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	32 Watts (Lamps ON) 0.4 Watts (Lamps OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D50 (Gen 1) C ₀ =D80 C ₉₀ =D80 (Gen 2)
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
1310060	1x14-35w Elect Ballast Multiwatt, A2
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

