


**CLEVERTRONICS L10 ARGONAUT LED WEATHERPROOF BATTEN**

Gen 1



Gen 2

PRODUCT INFORMATION

Catalogue Number	LWB2LEDS-P-ZW
Description	L10 Optimum 2ft Argonaut Weatherproof Batten with LED Emergency POD
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless Steel Clips with Tamperproof Screws
Mounting	Surface Mount
Dimensions L x W x H	660mm x 120mm x 108mm
Weight	2.2kg
Operating Mode	Sustained
Testing System	Zoneworks computerised testing
Battery	Lithium Nanophosphate, 3.2V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	OSRAM OTe, 50,000hr
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2000 lm @ 91lm/W
Power Consumption	22 Watts (Standby), 0.4 Watts (Lamps OFF)
IP Rating	IP66 (Batten), IP65 (POD)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D50 (Gen 1) C ₀ =D80 C ₉₀ =D80 (Gen 2)
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
8002685	PCA:LED Strip Argonaut Stand & tray,0.6m
1330025	LED Driver - Argonaut 25/220 CS
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8001450	PCA:Powerline Node ZW, #CT10310-A6

