



CLEVERTRONICS L10 ARGONAUT PRO LED WIDE BODY WEATHERPROOF BATTEN



Gen 1



Gen 2

PRODUCT INFORMATION

| | |
|-----------------------|--|
| Catalogue Number | LWB4LEDS-P-WB-PRO |
| Description | L10 Optimum, 4ft Argonaut PRO LED Weatherproof Batten with LED Emergency POD, Enabled with Clevertest Plus |
| Construction | Glass Fibre Reinforced (GRP) Base, Polycarbonate Diffuser with Aluminium Gear Tray and Stainless Steel clips |
| Mounting | Surface Mount |
| Dimensions L x W x H | 1332mm x 158mm x 100mm |
| Weight | 4.1kg |
| Operating Mode | Sustained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | Polycarbonate |
| Driver | OSRAM OT FIT 35/220-240/700 CS L |
| Lamp(s) | LED module, 4,000K Natural White, Ra>80, 44,000h Life [L80/B20 Ta 40°C], 50,000h Life [L70/B10 Ta 40°C] |
| Operating Voltage | 240V AC; 50Hz |
| Power Factor | 0.95 |
| Total lumen output | 4080 lm @ 123lm/W (based on the non-emergency version) - Default 3100 lm @ 115lm/W (Selectable during installation by dip switch on driver) - Low output mode |
| Power Consumption | 33 Watts (Lamp ON), 0.4 Watts (Lamp OFF) - Default 27 Watts (Lamp ON), 0.4 Watts (Lamp OFF) - Low output mode |
| IP Rating | IP66 (Batten), IP65 (POD) |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C ₀ =D63 C ₉₀ =D50 (Gen 1) C ₀ =D80 C ₉₀ =D80 (Gen 2) |
| Impact Rating | IK07 (Base), IK09 (Diffuser) |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|------------------------|--|
| 1530050 | BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT |
| 1330035 | LED Driver - Argonaut Low Output |
| 8002670 | PCA:40 LED Strip 600mm for Argonaut PRO |
| LLIFE-PRO-CKIT-L850-NP | LifelightPro,Control Only,Batten,L10, NP |

