

CLEVERTRONICS L10 WEATHERPROOF EXIT



PRODUCT INFORMATION

Part Number	LWELED-ZW
Description	L10 Lithium Nanophosphate weatherproof Emergency EXIT
Construction	Polycarbonate clear cover, Glass reinforced nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =E2 C ₉₀ =E2
Impact Rating	IK10
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
8002330	PCA:LCFLED Driver. #CT10164-L4.
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1
8001450	PCA:Powerline Node ZW, #CT10310-A6

