

CLEVERTRONICS TEMPORARY CLEVERFIT EXIT



PRODUCT INFORMATION

Part Number	TCFLED-LI
Description	Temporary Cleverfit Exit with flex and plug - for temporary lighting applications on construction sites
Construction	ABS Body and Diffuser with Polycarbonate clear decal cover and 1m flex and plug
Mounting	Chain Suspension (Bracket for Ceiling Mount is supplied) or Wall mount
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.2kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 600mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	4 x LED lamp bar assembly 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.1 Watts (Standby), 2.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D2 C ₉₀ =C2
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550195	BATT: LiFePO4 3.2V 600mAh 210mm lead, noBRKT
8002881	PCA:Driver ECFLED-LI CT10240-L6 4C40 M/NM CF 345

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

TEMP LITHIUM IRON
PHOSPHATE
TEMPORARY