

CLEVERTRONICS TEMPORARY CLEVERFIT EXIT



PRODUCT INFORMATION

Catalogue Number	TCFLED
Description	Temporary LED Cleverfit Exit with flex and plug - for temporary lighting applications on construction sites
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Suspended or Wall mount
Dimensions L x W x H	355mm x 80mm x 215mm
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Charging Method	Constant Current (16hrs), Pulse Charge (standby)
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	4 x LED lamp bar assembly 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.0 Watts (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Emergency Classification	C ₀ =D4 C ₉₀ =E2.5 (Expected) in accordance with AS/NZS 3012 and AS2293.3
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1510340	4xAA NiCad Batt Pk,4.8V,600mAh, cube
8002860	PCA:Driver for TCFLED. HT10150-C2
8002850	PCA:LED Strip for TCFLED. HT10153-A3

Temporary