

## CLEVERTRONICS LP JUMBO LED EXIT UNIVERSAL MOUNT (ZONWORKS XTHIVE)



### PRODUCT INFORMATION

Catalogue Number	CJELED-40-HV
MIC	AUA02810050001
Description	LP Premium Jumbo Emergency Exit
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Surface Mount
Dimensions L x W x H	630mm x 320mm x 100mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	Zoneworks XTHIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D6.3 C <sub>90</sub> =E3.2
Viewing Distance	40m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
8002470	PCA:Duris E5 Strip for LJELED.CT10050-D1
CJELED-40-CKIT-110	Jumbo LED Exit, Control Kit, LP
8003190	PCA: RF Node CT10678-Ax internal antenna

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*