



## LJELED-40

### CLEVERTRONICS L10 JUMBO UNIVERSAL MOUNT LED EXIT



#### PRODUCT INFORMATION

Part Number	LJELED-40
MIC	AUA01310260001
Description	L10 Optimum Jumbo Emergency Exit, Enabled with Clevertest Plus
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Universal Mount
Dimensions L x W x H	630mm x 100mm x 320mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box (One box solution)
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar – 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max, during first 16hr charge)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D6.3 C <sub>90</sub> =E3.2
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

#### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, Brkt
8002470	PCA:Duris E5 Strip for LJELED. CT10050-D2
AUM01370050001 LJELED-40-CKIT-110	Jumbo LED Exit, Control Kit, L10

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.