

Clevertronics Maintained IP65 Surface Mount Emergency with twin Lifelight Pro LED POD



PRODUCT INFORMATION

Catalogue Number	LWP2LIFEM-PRO-WPPOD-ZW-4HR
Description	Surface Mounted IP65 Maintained emergency luminaire with twin LED POD, L10 Lithium Nanophosphate batteries. 4 hour emergency duration.
Mounting	Surface Mount IP65 with integral lamp head, charger pack and battery
Dimensions L x W x H	L=520mm, W=180mm, H= 135mm
Operating Mode	Maintained (permanently)
Testing System	Zoneworks Computerized Testing
Ballast	Electronic
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	2 x 3W LED (50,000 hours L70/B50)
Operating Voltage	240V 50Hz
Power Consumption	11.4 W standby (after first 16 hours) 16.6 W max (at start of charge)
IP Rating	IP65
Operating Temperature	0°C to 40°C (Ambient)
AS2293 Classification	C0=D100, C90=D100

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	4 x Battery, 3.3 Volt 5Ah Li-ion
8002390	2 x Driver, PCA: ZONEWORKS Compatible
8001450	2 x Network, Zoneworks Powerline Node
110083X	2 (2 x 3W) LED Assembly