

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN & MICROWAVE SENSOR (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	CBS2LEDS-DIF-MS-HV
MIC	AUB02810120001
Description	LP Premium Quantum LED diffused batten with LED Emergency Pod and microwave sensor control of the lamps (on/off)
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	664mm x 120mm x 108mm
Weight	2.0 kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	Driver: 40w, 500-1050mA, 15-50V
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2187lm
Power Consumption	24W (MAX Charge - Lamp ON), 21W (Standby Lamp ON), 1.0W (Standby Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330029	LED Driver 40w, 500-1050mA, 15-50V
1190117	SENSOR: Microwave Motion IP20 MC602S
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
8001390	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order